






AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS





AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Technical specifications

Plug 'n play ECU for :

AiM ECU Taipan K Compatible models	Bike models				
	Brand	Type	Race	From Year	To Year
	KTM	SX 125	Cross	2024	2025
		SX 250	Cross	2024	2025
	HUSQVARNA	TC 125	Cross	2024	2025
		TC 250	Cross	2024	2025
	GASGAS	MC 125	Cross	2024	2025
		MC 250	Cross	2024	2025

Additional characteristics to the stock ECU:

- Two 0-5V analog inputs sampled @ 1,000 Hz each, could be alternatively used as switch to ground
- One low side driver (1A)
- 1 CAN bus for calibration purposes
- IMU
- Pitch/Roll
- Power consumption 150 mA
- Connectors: n.1 JST 04T-JWPF-VSLE-S connector
n.1 JST 08R-JWPF-VSLE-D connector
n.1 64 pins male connector
- Body: PA6 + 30% glass fiber + EPDM cover
- Dimensions: 112x100x40.8 mm
- Weight: 390 g approx
- Waterproof: IP67




AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Part numbers (ECU Taipan K & accessories)

XE1ECUTK0	ECU Taipan K
XE1HBS200	HBS2 (cable V02596160 is necessary)
V02596160	CAN + EXT Power Taipan K cable
X08CANBTM00	CAN-BT Module + ECU AiM Harness 40 cm
XE1UCB000	UC Bridge
XE1UCBT00	UC Bridge Tuner

Pinout






AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Functional diagram






AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Optional cables


1 UC Bridge extension cable 2 m

Part number V02596020




2 UC Bridge extension cable 4 m

Part number V02596030



3 Solo 2 DL/ECULog extension cable 50 cm

Part number V02589120






AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Optional cables


4 Analog channels harness

Part number V02596070




5 CAN + EXT Power Taipan K cable

Part number V02596160



6 Solo 2 DL/ECULog CAN + EXT power Taipan K cable

Part number V02589180






AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:

HBS2 (Handle Bar Switch 2)



Dimensions in mm [inches]



AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:

HBS2 main features

- Map selection: Up to 5 selectable maps
- Fuel Correction: for low, middle, and high RPM
- Launch control at different levels
- Traction control at different levels
- Enable quickshift using the button on models equipped with a factory electronic shifter


Technical specifications

Connector	1 JST 04T-JWPF-VSLE-S waterproof connector for CAN BUS communication
Body	PA6 + 30% glass fiber + silicon rubber
Dimensions	43.2x27.1x38.0 mm
Waterproof	IP67
Weight	70 g

Part number

XE1HBS200	HBS2
------------------	------

Pinout









AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:

CAN-BT Module



Dimensions in mm [inches]



AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:

CAN-BT Module Technical specifications

CAN-BT Module grants instant access to key engine data from your Taipan and Yarara ECU.


Installing the **SPARK App** (for Apple iOS and Android) on your smartphone provides a streamlined, data-driven interface for real-time monitoring of live engine parameters.

External power	9÷15 V
Connections	CAN, Bluetooth
Connectors	1 Binder 712 female
Material	PA6 30% glass
Dimensions	44.0 x 38.0 x 19.8 mm
Weight	50 g
Waterproof	IP65

Part number

X08CANBTM00	CAN-BT Module + ECU AiM Harness 40 cm
--------------------	---------------------------------------

Pinout





AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:


UC Bridge



User license



Tuner license





AiM ECU Taipan K & accessories

PLUG 'N PLAY ECU FOR MOTOCROSS

Accessories:

UC Bridge technical specifications

Connections	n.1 USB connection for PC
	n.1 JST 04R-JWPF-VSLE-S waterproof Connector for CAN Bus communication
Body	PA6 + 30% glass fiber
Dimensions	103.5x45.3x18.1 mm
Waterproof	IP65
Weight	80 g

Part numbers

XE1UCB000	UC Bridge
XE1UCBT00	UC Bridge Tuner

Pinout

